



6' LONG CABLE w/ 3.5mm MONO JAX
 0-4Vdc 1.2 AMP MAX
 LUMINOUS INTENSITY
 3200 mcd
 REQUIRES FRESNEL LENS ATTACHMENT

OUTLINE

USED ON:		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		P/N SUFFIX DEFINITION		<div>NAVITAR</div> <div>ROCHESTER, NEW YORK</div>		
MATERIAL:				-1 CONVERSION COATING -2 PAINTING -3 MARKING -R REWORK				
FINISH:		TOLERANCES AS FOLLOWS		SCALE: 1:1		<div>WHITE 60 LED RING LIGHT</div>		
		DEC. .XXX ± .005		DR: DJM				
		DEC. .XX ± .010		CH: PB				
		FRACT. ± 1/64		APP: PB				
		ANGLES ± 30°		DATE DR: 11/15/2002				
CONCENTRICITY .003 TIR		DO NOT SCALE DRAWING		<div><div>0.0inch1.0</div><div>0.0mm25.0</div><div></div></div>				
BREAK ALL SHARP EDGES .005 MIN. .010 MAX.								
CHAMFER ALL THREADS 30° TO ROOT DIAMETER		MAX. SURF. ROUGHNESS: 32		SIZE		1-62350_OL		REV
				A		SHEET 1 OF 1		A