



OUTLINE

| | | | | | | | |
|---|---|---------------------|----------------------|--|--|---------------------------------------|-----------------|
| USED ON: | UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES | | | P/N SUFFIX DEFINITION -1 CONVERSION COATING -2 PAINTING -3 MARKING -R REWORK | | NAVITAR ROCHESTER, NEW YORK | |
| MATERIAL: | | | | | | | |
| FINISH: | TOLERANCES AS FOLLOWS DEC. .XXX ± .005 DEC. .XX ± .010 FRACT. ± 1/64 ANGLES ± 30° CONCENTRICITY .003 TIR BREAK ALL SHARP EDGES .005 MIN. .010 MAX. MAX. SURF. ROUGHNESS: 32 ✓ | SCALE: 1:1 | DR: DJM | 0.0 inch 1.0 0.0 mm 25.0 | | 100mm W.D. FRESNEL LENS ATTACHMENT | |
| CHAMFER ALL THREADS 30° TO ROOT DIAMETER | | CH: PB | APP: PB | | | | |
| | | DATE DR: 11/15/2002 | DO NOT SCALE DRAWING | | | SIZE A | REV A |
| | | | | | | 1-62357_OL SHEET 1 OF 1 | |